

Model BM 2,4-10

Plug and Play



Technical Range

Crane type	BM 2,4-10
Design life	25 years
OSWL range	1000 kg
Outreach range	2,4 meters
Hoisting travel	26 meters
Hoisting speed	2 speed solution with up to 40 m/min in Speed II
Adjustable slewing angle	355° ltd
Slewing speed	Manual slewing
Slack rope protection	Yes
Weight in total	Approx. 1250 kg

General Operation	PLUG and Play solution
	Integrated starter cabinet and remote control inside crane and ready for use

Electrical system	
Power supply	3X690VAC/50 Hz or 3x400VAC/50 Hz

Safety systems	All cranes have AOPS, MOPS and HOPS safety systems
-----------------------	--

Working conditions	
Wind speed	15m/sec
Sea state	Up to 2,0 meters

Surface Treatment	Hot galvanised and according to Corrosion Class C5M according ISO 12944-5
--------------------------	---

Approvals	CE marked and according to Machinery directive Class or other approvals on request
------------------	--

Down bendable jib

The crane is offered with down bendable jib as standard. This gives the possibility for customer to reach lifting points or jib head from deck level. This also makes it possible to get easier access to essential key components inside the crane from deck level.

Other design figures of the crane

We offer a crane with a unique design that gives the possibility to protect all essential key components inside the crane structure. The interior of the crane house is treated with an extra anti condensation/corrosion treatment.